

lumilight

FICHA TÉCNICA

PAINEL ENCASTRAR REDONDO 18W ARO BRANCO

Painel de Encastrar, ideal para tectos falsos com altura limitada.

43452



REFERENCE

Led Type	SMD
Mounting Type	Recessed
Body Material	Aluminium
Housing Colour	White
Body Shape	Round
LGP	PS
Nominal Lifetime (EOL end of life)	20000hrs
LED Type	2835 LED
Useful Lifetime Based on LM70	-
Dimmable	No

DIMENSION & WEIGHT

Lenght	Ø220mm
Width	Ø220mm
Height	20mm
Weight	0.275kg
Cut-Out	Ø200mm

PHOTOMETRICAL DATA

Total Luminous Flux	1640lm
Luminous Efficacy	90lm/w
Beam Angle	120°
Colour Temperature	6400/4200k/3000K
Colour Rendering Index	>80
Colour Consistency	<= 6
UGR	

ELECTRICAL AND OPERATING DATA

Nominal Wattage	12W
Nominal Voltage	85-265V
Operating Frequency	50/60Hz
Power Factor	0.9
Operating Temperature	- 20° C to + 40° C

ENERGY LABEL & STANDARS

Energy Label	A+
Energy Consumption KWH/1000H	12kwh
Type of Protection	IP44
Protection Class	II
Protecion Class IK (shock resistance)	-

CERTIFICATIONS

2014/30/EU (EMC Directive)	YES
2014/35/EU (LVD Directive)	YES
ROHS	YES
Warranty	2 YEARS

SIZE

