

# lumilight

## FICHA TÉCNICA

### APLIQUE MURO IP65 6W 4200K BRANCO

Luminária de exterior com design moderno e luz indireta com placa smd integrada. Materiais em Aluminum ABS PC com tratamento anticorrosivo e proteção IP65.

Outdoor lamp with a modern design and indirect light with integrated smd plate.

Aluminum materials with anti-corrosion treatment and IP65 protection.



65973

REFERENCE		DIMENSION & WEIGHT		PHOTOMETRICAL DATA	
Reference	65973	Lenght	230mm	Total Luminous Flux	120lm
LED Type	SMD	Width	80mm	Luminous Efficacy	60lm/W
Body Material	Aluminium	Height	27mm	Beam Angle	32°
Housing Colour	White	Packaging Unit	20PCS	Colour Temperature	4200K
Nominal Lifetime (EOL end of life)	20000H	Gross Weight	6 kg	Colour Rendering Index	>80
Surface/Recessed	Surface	Volume	20 dm <sup>3</sup>		
Dimmable	NO				

ELECTRICAL AND OPERATING DATA		ENERGY LABEL & STANDARS		CERTIFICATIONS	
Nominal Wattage	6W	Energy Label	A+	2014/30/EU (EMC Directive)	YES
Nominal Voltage	220-240V	Energy Consumption KWH/1000H	5 kwh	2014/35/EU (LVD Directive)	YES
Operating Frequency	50/60Hz	Type of Protection	IP65	ROHS	YES
Operating Temperature	- 25° C to + 45° C	Protection Class	Class II	Warranty	2 YEARS
Starting Time 100% ON	<0.5s	Proteccion Class IK (shock resistance)	IK08		
ON/OFF Cycles	>20000				

